

EW5614

Pulverizador de contacto para limpeza a seco

Pulverizador de contacto para limpeza a seco para contactos elétricos

- Desoxidante seco para contactos elétricos
- Evita a entrada de humidade
- Não deixa resíduos
- Evapora rapidamente
- 100% Ozônio amigável
- Conteúdo: 200ml

DESCRIPTION

Ewent EW5614 Desoxidante seco para contactos elétricos ideal para grupos de controlo e sensores eletromecânicos.

TECHNICAL

- Mixture of aliphatic solvents and alcohols with the addition of propellant (LPG).
- Does not deplete the ozone layer;
- Non-corrosive;
- Contains corrosion inhibitor;
- Safe on all metal surfaces, does not stain;
- Safe on most tires, plastics and coatings. Before use, perform a test on sensitive or highly stressed materials.
- Packaging: aerosol
- Color: Colorless
- flammability: extremely flammable
- net content: 200ml
- storage temperature: between +10°C and +30°C

LOGISTIC

- Product Weigth: 219.00 g
- Retail packaging Dimension (mm): 50 x 175 x 50
- Retail packaging Weigth: 224 g
- Master carton Qty: 12
- Master carton Dimension (cm): 22 x 16 x 18
- Master carton Weigth: 2.50 kg



Dry cleaner for electrical products.

