

EW5616

Spray Raffreddante

Spray Raffreddante per rilevare i difetti dovuti al surriscaldamento delle schede elettroniche

- Raggiunge -45°C
- Ricerca i difetti dovuti al surriscaldamento
- Riduce i danni dovuti alla saldatura o alla brasatura
- Rispetto dellozono al 100%
- Contenuto 200ml

DESCRIPTION

Ewent EW5616 Spray raffreddante istantaneo ideale per rilevare i difetti dovuti al surriscaldamento delle schede elettroniche e dei difetti di saldatura.

TECHNICAL

- Contains flammable light gases (propane-butane). Ecological and odorless product.
- Does not affect plastic materials and leaves no residual moisture
- High pressure removes dirt easily and quickly
- Spray with special valve for air flow control
- Does not contain propellants deemed harmful to ozone
- Packaging: Aerosol
- Color: Colorless
- flammability: Extremely flammable
- net content: 200ml
- storage temperature: less than 50°C

LOGISTIC

- Product Weight: 155.00 g
- Retail packaging Dimension (mm): 50 x 160 x 50
- Retail packaging Weight: 160 g
- Master carton Qty: 12
- Master carton Dimension (cm): 16 x 22 x 18
- Master carton Weight: 2.00 kg

