

EW7077

USB-C 3.2 Gen2 2.5 inch RAID Dual HDD/SSD enclosure

Aluminium SATA enclosure with RAID 0/RAID 1/JBOD/BIG mode

- Aluminium RAID enclosure for two 2.5 inch SATA SSDs/HDDs with a max. height of 9.5mm with RAID 0/RAID 1/JBOD/BIG modes
- Perfect for securing your data for drive failures
- USB powered; comes with a USB-C to USB-C cable and USB-C to USB-A cable
- UASP support for a higher data transfer speed
- Backwards compatible with USB 3.1 Gen1, 3.0, 2.0
- Comes with a stand, rubber feet, screwdriver and screws
-

DESCRIPTION

The EW7077 USB-C RAID Dual HDD/SSD Enclosure lets you mount two HDDs or SSD's with a max. height of 9.5mm in ONE enclosure. This is perfect for securing your data in case of drive failure. The USB-C 3.2 Gen2 enclosure supports RAID 0, RAID 1, JBOD and BIG/SPAN. A USB-C to USB-C cable and USB-C to USB-A cable, standard, rubber feet, screwdriver and screws are enclosed. The EW7077 supports UASP for higher data transfer speed and is backwards compatible with USB 3.2 Gen1, USB 3.1 Gen2, USB 3.1 Gen1, USB 3.0 and USB 2.0.

Protect your data with RAID 1

Store two 2.5 inch SATA SSDs and HDDs (with a max. height of 9.5mm) in the EW7077 USB-C Enclosure. This enclosure supports RAID 0, RAID 1, JBOD, BIG/SPAN. Choose the desired RAID mode by adjusting the DIP switches. Protect your data when a drive gets corrupt by choosing RAID 1 (Mirroring). The fastest read/write option is RAID 0 (Striping). For the biggest capacity you need to choose for JBOD or BIG/SPAN. SuperSpeed USB 10Gbit/s support

The EW7077 enclosure supports UASP (USB Attached SCSI-Protocol) and SuperSpeed USB 10Gbit/s which enables you to transfer data at a maximum rate up to 10Gbit/s. Complete solution

Use the enclosed screws and screwdriver to build in the SSDs or HDDs. The enclosure is provided with both a USB-C to USB-C and a USB-C to USB-A cable, a stand and USB power cable.

TECHNICAL

- Material: Aluminum
- Interface: Compliant with USB 3.2 Gen2 specifications (up to 10Gbps)
- RAID Support: Yes
- RAID modes: RAID0, RAID1, JBOD, SPAN
- Supports UASP protocol for faster USB 3.2 performance
- Application: HDD or SSD SATA I, II, III 2.5 inch up to 9.5mm
- Comes with: USB-C to C and USB-C to A cable
- Power: DC 5V via USB cable (included)
- Optional Power Supply 5V 2A (not included): AC1505
- Cable length: 45cm
- Led Indicator: 2x Power/Activity/Status (Blue)
- Dimensions (WxHxD): 25x83x130mm
- Weight: 192g
- Colour: Black

LOGISTIC

- Product Weight: 350.00 g
- Retail packaging Dimension (mm): 185 x 135 x 50
- Retail packaging Weight: 355 g



- Master carton Qty: 20
- Master carton Dimension (cm): 0
- Master carton Weigth: 0.00 kg

