

IM1228

Cable de instalación CAT.7 S / FTP, LSZH, 305m

- AWG23 / 1
- CU desnudo sólido
- Chaqueta: LSZH de color naranja
- Certificado por CPR, Clase B2ca Eca
- Rendimiento de 1200MHz
- 10Gbit Ethernet
- PoE Power over Ethernet support

DESCRIPTION

El cable de instalación S/FTP Cat.7 de Ewent sigue la construcción del cable 4x2x AWG23/1 y alcanza una frecuencia de transmisión de hasta 1200 MHz. La cubierta del cable libre de halógenos cumple con los estándares IEC 60332-1, FRNC-B, LSZH-1 y CPR Euro class Eca. El cable es apto para la construcción de cableado estructurado en el área secundaria y terciaria. Cumple con las siguientes normas ISO/IEC 11801, DIN EN 50173, DIN EN 50288-11-1.

TECHNICAL

- Category: Cat.7
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Conductor
- Conductor material: CU (Copper)
- Conductor size (AWG): 23/1
- Conductor type: Solid
- Diameter: 0.57mm (+/- 0.005mm)
- Outer Jacket
- Jacket material:LSZH
- CPR: B2ca Eca
- Thickness: 0.56mm (+/- 0.05mm)
- External diameter: 7.3mm (+/- 0.5mm)
- Cable length: 305m
- Color: orange


LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:





CAT.7
S/FTP



PURE BARE COPPER