

EW1564

Fascette in nylon nero, 200 mm x 2,5 mm

- Set di fascette (100 pezzi) in poliammide altamente robusto per uso interno ed esterno, resistente ai raggi UV (UV ASTM D6779).
- Utilizzo in ingegneria meccanica, ingegneria elettrica, artigianato, edilizia, agricoltura, orticoltura e per tutti gli appassionati di fai da te
- Resistente a: grassi, detersivi, prodotti raffinati, solventi clorurati, alcoli e fenolo.
- Il prodotto soddisfa tutti gli standard europei, è certificato UL.
- Resistenza alle alte temperature: da -40 °C a +85 °C (temperatura di applicazione: -40 °C / +85 °C, temperatura di installazione: -10 °C / +60 °C, temperatura massima di esercizio: +/-60 °C, temperatura di fusione +256 °C).

DESCRIPTION

TECHNICAL

LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:



Desirable Design

self-locking fastener design binds multiple cables as a whole

53mm maximum bundle diameter

Premium Quality & Sturdy Texture

super strong & durable nylon supports up to 8kg weight capacity

Versatility

used under indoor & outdoor settings for multiple purposes

Multi-purpose

Chemical Resistance

resistant to chemical substance of low intensity

UV & Heat Resistance

resistant to UV & high temperature

Against UV Rays
UV-resistant

Against Heat
high temperature resistant

Maximum application diameter: 53mm

53mm

2000mm

Thickness: 0.8mm

Strength tensile is decided by width and thickness