

Safety Data Sheet dated 22/5/2019, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PERMANENT GLUE SPRAY

Trade code: EW5626

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Glue spray

Uses advised against:

do not use on humans and animals

1.3. Details of the supplier of the safety data sheet

Company:

ALBINA S.R.L. - Via Crocevia, 12 - 39057 - Appiano sulla strada del Vino (BZ)

ALBINA S.R.L. - info@ewent-online.com

Competent person responsible for the safety data sheet:

info@ewent-online.com

1.4. Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)

Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

- ♦ Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2, Causes serious eye irritation.
- Warning, STOT SE 3, May cause drowsiness or dizziness.
- Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... Thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P391 Collect spillage.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

hydrocarbons c7, n-alkanes, isoalkanes, cyclics

acetone; propan-2-one; propanone

derogation 1.3.3. Aerosols and containers fitted with a sealed spray device and containing substances or mixtures classified as hazardous in the event of aspiration

As regards the application of point 3.10.4, substances or mixtures classified according to the criteria set out in points 3.10.2 and 3.10.3 do not necessarily bear on the label indications relating to this danger when they are placed on the market in aerosol containers or in containers fitted with a sealed spray device

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

Product contents:

Aliphatic hydrocarbons

15 - 30 % The product also contains:

Allergens:

Preservatives:

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

section 10.3

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 25% - < 30%	hydrocarbons c7, n- alkanes, isoalkanes, cyclics	CAS: EC: REACH No.:	64742-49-0 927-510-4 01- 2119666169- 27-0000	2.6/2 Flam. Liq. 2 H225 3.2/2 Skin Irrit. 2 H315 4.1/C2 Aquatic Chronic 2 H411 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336
>= 15% - < 20%	propane	Index number: CAS: EC: REACH No.:	601-003-00-5 74-98-6 200-827-9 01- 2119486944- 21-0046	
>= 10% - < 12.5%	Hydrocarbons, C4; Petroleum gas	Index number: CAS: EC: REACH No.:	649-113-00-2 87741-01-3 289-339-5 01- 2119480480- 41-xxxx	2.5 Press. Gas H280 2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
>= 10% - < 12.5%	acetone; propan-2- one; propanone	Index number: CAS: EC: REACH No.:	606-001-00-8 67-64-1 200-662-2 01- 2119471330- 49-xxxx	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336 EUH066

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to the contained substances see chapter 11

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Follow the doctor's instructions.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Water

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Normal elements for fire fighting, such as a self-contained compressed air open-circuit respirator (EN 137), fire-retardant suit (EN469), flame-retardant gloves (EN 659) and fire boots (HO A29 or A30).

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains

Keep containers cool with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Wash with plenty of water.

Wet clean or vacuum up solids.

Clear spills immediately

Other information:

Don't use a brush or compressed air for cleaning surfaces or clothing.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

at work do not eat or drink.

avoid the accumulation of electrostatic charges.

do not smoke

Always keep in a well ventilated place.

Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

```
8.1. Control parameters
```

```
hydrocarbons c7, n-alkanes, isoalkanes, cyclics - CAS: 64742-49-0
```

TLV-ACGIH - Notes: TLV TWA - 400ppm-1639,26 mg/m3 (ACGIH)

TLV STEL - 500ppm-2049,08 mg/m3 (ACGIH)

propane - CAS: 74-98-6

ACGIH

acetone; propan-2-one; propanone - CAS: 67-64-1

EU - TWA(8h): 1210 mg/m3, 500 ppm

ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm

DNEL Exposure Limit Values

hydrocarbons c7, n-alkanes, isoalkanes, cyclics - CAS: 64742-49-0

Worker Professional: 300 mg/kg/d - Exposure: Human Dermal - Frequency: Long

Term, systemic effects

Worker Professional: 2085 mg/l - Exposure: Human Inhalation - Frequency: Long

Term, systemic effects

Consumer: 149 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic

effects

PNEC Exposure Limit Values

N.Ä.

8.2. Exposure controls

Eye protection:

Basket eye glasses (standard EN 166)

Protection for skin:

Wear work clothes with long sleeves and protective footwear for professional use of category II (ref.Directive 89/686 / CEE and norm EN ISO 20344). Wash with soap and water after removing protective clothing.

Protection for hands:

Protect hands with category II work gloves (ref. Directive 89/686 / EEC and standard EN 374). Use PVC or nitrile rubber gloves.

Respiratory protection:

if the TLV thresholds are exceeded, use a mask with filter type A (against vapors of organic compounds) in accordance with EN 141.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can		
Odour:	characteristic		
Odour threshold:	Not Relevant		
pH:	Not Relevant		
Melting point / freezing point:	Not Relevant		-
Initial boiling point and boiling range:	Not Relevant		-
Flash point:	< 0 ° C		
Evaporation rate:	Not Relevant		
Solid/gas flammability:	Not Relevant		
Upper/lower flammability or explosive limits:	Not Relevant		-
Vapour pressure:	4 bar +/- 1 20°C		
Vapour density:	>2		
Relative density:	0.7125 +/- 0.05 g/l		-
Solubility in water:	Not Relevant		
Solubility in oil:	Not Relevant		
Partition coefficient (n-octanol/water):	Not Relevant		-
Auto-ignition temperature:	>175°C		
Decomposition temperature:	Not Relevant		
Viscosity:	Not Relevant		
Explosive properties:	section 10.3		
Oxidizing properties:	Not Relevant		

9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	Not Relevant		

Miscibility:	Not Relevant		
Fat Solubility:	Not Relevant		
Conductivity:	Not Relevant		
Substance Groups	Not Relevant		
relevant properties			

SECTION 10: Stability and reactivity

10.1. Reactivity

avoid contact with strong acids and bases and oxidizing agents.

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

may form explosive vapor / air mixtures in places not well ventilated

10.4. Conditions to avoid

avoid the accumulation of electrostatic charges.

keep away from heat, sources of ignition

10.5. Incompatible materials

oxidizing agents

acids, alkalis and alkaline metals

10.6. Hazardous decomposition products

during combustion it produces irritating gases

by thermal decomposition can rid COx

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

COLLA PERMANENTE 400ML

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

hydrocarbons c7, n-alkanes, isoalkanes, cyclics - CAS: 64742-49-0

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 23300 mg/m3 - Duration: 4h

Test: LD50 - Route: Skin - Species: Rat > 2920 mg/kg Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg

acetone; propan-2-one; propanone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

COLLA PERMANENTE 400ML

The product is classified: Aquatic Chronic 2 - H411

hydrocarbons c7, n-alkanes, isoalkanes, cyclics - CAS: 64742-49-0

a) Aquatic acute toxicity:

Endpoint: EL50 - Species: Fish = 1.5 mg/l - Duration h: 48 Endpoint: LC50 - Species: Daphnia = 4 mg/l - Duration h: 24

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

CER 160504

contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management

reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local.

SECTION 14: Transport information

14.1. UN number

ADR-UN number: 1950 IATA-Un number: 1950 IMDG-Un number: 1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950

IATA-Class: 2.1

IMDG-Class: 2 Aerosols UN 1950

14.4. Packing group

ADR-Packing Group: N.A. IATA-Packing group: N.A. IMDG-Packing group: N.A.

14.5. Environmental hazards

Marine pollutant: Marine pollutant

14.6. Special precautions for user

IMDG-Page: 2102

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P3a, E2

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.